


ROHS

A - coded								
B - coded								
D - coded								



cable color

- P1 color
- PIN1 — Brown
 - PIN2 — White
 - PIN3 — Blue
 - PIN4 — Black

ITEM	NAME	SPECIFICATION	UNIF	Q'TY	PIN	Rated voltage	Rated impulse voltage	Rated current	Contact resistance	Wire gauge (mm ² / AWG)	Degree of protection
⑤	Insulator	PA66+30%GF black	PCS	1		250V	2500V	4A	≤3mΩ	0.25mm ² / 24	IP67/IP68
④	Terminal	Ø0:1.0 copper alloy	PCS	4		125V	1500V	4A	≤3mΩ	0.25mm ² / 24	IP67/IP68
③	Screwnut	M12X1.0 Male Nut Brass Nickel Plated	PCS	1		60V	800V	2A	≤3mΩ	0.25mm ² / 24	IP67/IP68
②	Overmold	Black 45P PVC material	G	12		30V	500V	1.5A	≤3mΩ	0.14mm ² / 26	IP67/IP68
①	Cable	UL2464 4C*22AWG Wire BROWN/WHITE/BLUE/BLACK JACKET:BLACK PVC L= MM	MM	L±10%		30V	500V	1.5A	≤3mΩ	0.14mm ² / 26	IP67/IP68

Undeclared tolerance		SPECIFICATION		M12-4 Pin A code Male Straight Connector		MaterialPVC		Quality	
0.5 - 3	±0.1	Design	YOYO	M12-4 Pin A code Male Straight Connector		MaterialPVC		Number: M12A4PMZT L M22AWG	
>3 - 6	±0.1	audit	ZZH					Quality percentage	
>6 - 30	±0.2	drawing	HSY					<input checked="" type="checkbox"/> Qua <input type="checkbox"/> Re <input type="checkbox"/> OF1	
>30-120	±0.3	counter sign	WGZ					First sheet	
>120-400	±0.5	amend	...					date:	
>400-1000	±0.8	approve	TFY						

Q'TY: pcs